



Expanded Camera Selection

TR-XT comes as standard for use with 8 or 16 camera channels. This is ideal for both smaller and mid-sized installations where simultaneous access to a number of cameras is required.

In some cases it is useful to be able to access a larger number of cameras simultaneously — especially systems where cameras may be located in multiple studios across WAN. Each Auxiliary Panel expands to an additional 16 camera selection keys on top of the main panel capacity.

In addition to adding greater camera capacity, the Aux panel by making use of LCD matrix keys, enables the key to carry a short description of the camera channel, rather than just a fixed number. It also supports dynamic mapping and camera number changing within the TR-XT system

Multiple Auxiliary Panels may be connected for further expansion capacity in groups of 16.

Full support of TR-XT camera mapping, and backup link operation.

Compatible with TR-XT, TR-S and TR-B panels with or without CCU expansion panels

FEATURES

- 19" x 1RU hardware panel
- Up to 16 additional camera selection keys
- May be in addition to the main panel or duplicating keys
- Backlit LCD matrix keys with dynamic legends
- POE network power

SPECIFICATIONS

Keys	16 x LCD matrix keys Full RGB LED backlight
Connections	2 x RJ45 network (100Mbps)
Size	19"x1RU
Power	POE 802.3af 10W max
Configuration	Via custom web interface

