

SD SE SERIES

SD20 SD40

FOR HD / 4K HANDHELD CAMERAS

The Shotoku SD range has been developed to provide a high-quality affordable support system for handheld cameras. The SD20 supports 3 kg (6.6 lbs), and the SD40 5kg (11 lbs), camera configurations.

The system features fixed counterbalance and drag systems tailored to the payload of the head. They come complete with extended range 2-stage tripod, mid-level spreader and soft carrying case.

SD20 SYSTEM

SD20 head + single fixed-length pan bar + 2-stage aluminum tripod + mid-level spreader w/foot pads + soft carrying case.

SD40 SYSTEM

SD40 head + single fixed-length pan bar + 2-stage aluminum tripod + mid-level spreader w/foot pads + soft carrying case.



FEATURES

Lightweight
Robust
Smooth Operation
Reliability



SD20 System

SPECIFICATIONS

	SD20	SD40
Payload Range	0 - 3kg / 0 - 6.6lbs	0 - 5kg / 0 - 11lbs
Pan Range	360°	360°
Tilt Range	+80° ~ -90°	+80° ~ -90°
Camera Fixing	Two-Way sliding quick-release plate with 1 x 1/4" screw + pin	Two-Way sliding quick-release plate with 1 x 1/4" screw + pin
Pan Bar	Single, Fixed-Length	Single, Fixed-Length
Mount	60mm Ball	60mm Ball
Temperature Range	-40° C to 50° C / -40° F to 122° F	-40° C to 50° C / -40° F to 122° F
Level	Bubble	Bubble
Tripod	2-Stage Aluminum	2-Stage Aluminum
Standard Spreader	Mid-Level	Mid-Level
System Height Range	780mm - 1625mm / 30.7" - 64"	780mm - 1625mm / 30.7" - 64"
System Transportation Length	820mm / 32.3"	820mm / 32.3"
System Weight	3.98kg / 8.77lbs	3.98kg / 8.77lbs