



Ultimate Flexibility

The TR-XT control system is designed to match the needs of any size of production, from a single camera studio up to a nationwide fully-integrated network of control rooms and studios. TR-XT offers a number of advanced control features yet is always simple to use even in highly-dynamic, multi-camera live broadcast conditions. Available with 8 or 16 camera configurations, and with the ability to expand to 32 via an expansion panel the system is easily scalable to future needs.

TR-XT consists of a dedicated hardware control panel, with single or dual joysticks, working closely with the TR-XT software and touchscreen. As with all Shotoku control systems the joystick and shot recall functions are always intended for on air use and features like joystick profiling, Orbit mode and LiveView make perfect movement easy to achieve, regardless of operating modes.

Resilience is built in through the Backup-Link function allowing control to continue even in the event of PC and/or Touchscreen fault.

FEATURES

- Touch Screen & Hardware Panel Operation
- Practically Unlimited Shots per Camera
- Practically Unlimited Number of Cameras
- CRuZe Unique Shot Recall Mode
- Multi-Shot Key-Frame Sequences
- AutoFrame Automatic Face Tracking option
- Intuitive LiveView Spotter Camera option

Multiple TR-XT systems may work together with a shared database of shows and shots, or independently with completely separate configurations to suit the control location, or operator preferences.

Shotoku's unique LiveView mode supports a secondary live video 'spotter' view from a wide angle IP camera, providing a truly interactive control UI based on live video touchscreen.

The TR-XT system supports the whole range of Shotoku heads, height drives, rail cameras and pedestals, VR/AR operations as well as the latest AutoFrame automatic tracking and framing system.

SPECIFICATIONS

Controls

3-axis proportional joystick (PTZ)
Rotary encoders for Focus, Time and Iris
Cut, Fade, CRuZe shot recall modes
LiveView Spotter camera support
Drag and Centre fingertip control
Orbit mode for easy SmartPed arc motion
8 or 16 Camera channels (main panel)
+16 Camera expansion panels (option)

Connections

On Air Tally (TSL/Serial/GPI)
Single/Dual Ethernet Network
Serial/IP Router control
IP Automation I/F
HD-SDI Video capture

Size

Panel: 19"x3RU
Computer: 19"x2RU
Touch Screen: 22" 16:9

Power

PC: 100-240 VAC 50/60Hz ~200W
Panel : +5VDC AC PSU Provided



Ultimate Expansion

The TR-XT control system is highly expandable, supporting 8,16,32 or even more cameras from a single control position. The main TR-T joystick panel has a maximum of 16 dedicated camera selection buttons, however an expansion camera select panel can be added, with LCD matrix-display keys enabling customised legends to be created. The key-top display can even be modified dynamically if automation systems require system configuration changes to the cameras available to any panel.

Versatile System Configuration

The TR-XT control system is easy to configure and very easy to build into large or small remote camera systems. Combining TR-XT with other controllers requires no direct interconnection, or modification to existing panels; simply connecting to the Shotoku network is enough. Even combining panels of other types (e.g. TR-B, TR-HP) is simple and all operators can work together seamlessly.

TR-XT, like all Shotoku panels, is able to maintain a Camera Map—defining the cameras which are 'visible' to the panel. This will often be all of the cameras in the system, but it could also be a sub-set, depending on the system requirements for shared cameras.

